DULL GRADE REPORT

 Operator
 EXXON MOBIL
 Bit Type

 Rig
 WEST ALPHA
 Bit Size

 Well
 25/11-C-3BH
 Serial No.

 Field
 BALDER
 IADC Code

	Inner	Outer	Condition	Location	Bearings	Gauge	Other	РООН
SDBS Dull:								ВНА
Rig Dull:	11CTGXINOB	НА			SBDS Dull Da	ite:		
Dull Remarks:								
Recommendation:	RERUNABLE							
Comments:								

No top view image

No side view image

FM2943RI/4

12 1/4"

M332

5971907

Depth In (m)	1042	Flow (lpm)	-	Mud Weight (sg)	1.4
Depth Out (m)	2090	WOB (ton)	-	Drive System	PDM
Meters	1048	RPM	-	Deviation in	31
Hours	67	Mud Type	OBM;ANCOTECH	Deviation out	51
ROP (m/hrs)	15.6	TFA (in2)	1.387	Max Dogleg	
TVD In (m)		TVD Out(m)			
Formation	TERT;ROGALAND,HORD	ALAND,BALDER		·	
Lithology	CLST, LST STRINGERS				

Run	Meters	Hours	ROP
	28	2.8	10
	1048	67	15.6
Total	1076	69	

DULL GRADE REPORT

EXXON MOBIL Operator Bit Type FM2943RI/4 Rig WEST ALPHA Bit Size 12 1/4" Well 25/11-C-3BH Serial No. 5971907 Field **BALDER** IADC Code M332

	Inner	Outer	Condition	Location	Bearings	Gauge	Other	РООН
SDBS Dull:								TD
Rig Dull:	11CTGXINOT	D			SBDS Dull Da	ite:		
Dull Remarks:								
Recommendation:	RERUNABLE							
Comments:								

No top view image

No side view image

Depth In (m)	2090	Flow (lpm)	-	Mud Weight (sg)	1.4
Depth Out (m)	2118	WOB (ton)	-	Drive System	PDM
Meters	28	RPM	-	Deviation in	51
Hours	2.8	Mud Type	OBM;ANCOTECH	Deviation out	51
ROP (m/hrs)	10	TFA (in2)	1.387	Max Dogleg	
TVD In (m)		TVD Out(m)			
Formation	TERT;ROGALAND				
Lithology	CLST, LST STRINGERS				

Run	Meters	Hours	ROP
	28	2.8	10
	1048	67	15.6
Total	1076	69	

DULL GRADE REPORT

EXXON MOBIL Operator Bit Type FM2943RI/4 Rig WEST ALPHA Bit Size 12 1/4" Well 25/11-B-11H Serial No. 5971907 Field **BALDER** IADC Code M332

	Inner	Outer	Condition	Location	Bearings	Gauge	Other	РООН
SDBS Dull:								ВНА
Rig Dull:	11CTNXINOB	HA			SBDS Dull Da	ite:		
Dull Remarks:								
Recommendation:	RERUNABLE							
Comments:	NOT ABLE TO	STEER, TOO	MANY LIMEST	STRINGERS				

No top view image

No side view image

Depth In (m)	1060	Flow (lpm)	-	Mud Weight (sg)	1.4
Depth Out (m)	1599	WOB (ton)	-	Drive System	PDM
Meters	539	RPM	200 - 300	Deviation in	0
Hours	44.7	Mud Type	OBM;ANCOTECH	Deviation out	30
ROP (m/hrs)	12	TFA (in2)	1.5	Max Dogleg	
TVD In (m)		TVD Out(m)			
Formation	HORDALAND,ROGALAND				
Lithology	CLST, LST STRINGERS				

Run	Meters	Hours	ROP
	539	44.7	12
Total	539	44	

DULL GRADE REPORT

EXXON MOBIL Operator Bit Type FM2943RI/4 Rig WEST ALPHA Bit Size 12 1/4" Well 25/11-B-14H Serial No. 5971907 Field **BALDER** IADC Code M332

	Inner	Outer	Condition	Location	Bearings	Gauge	Other	РООН
SDBS Dull:								ВНА
Rig Dull:	22CTNXINOB	HA			SBDS Dull Da	ite:		
Dull Remarks:								
Recommendation:	RERUNABLE							
Comments:	NOT ABLE TO	STEER, TOO	MANY LIMEST	STRINGERS				

No top view image

No side view image

Depth In (m)	998	Flow (lpm)	-	Mud Weight (sg)	1.4
Depth Out (m)	1673	WOB (ton)	-	Drive System	PDM
Meters	50.7	RPM	200 - 340	Deviation in	45
Hours	1	Mud Type	OBM;ANCOTECH	Deviation out	58
ROP (m/hrs)	13	TFA (in2)	1.5	Max Dogleg	
TVD In (m)		TVD Out(m)			
Formation	HORDALAND,ROGALAND				
Lithology	CLST, LST STRINGERS				

Run	Meters	Hours	ROP
	50.7	1	13
Total	50.70000 0000000 0028421 7094304 0400743 4844970 703125	1	